



TY-12.5M 3P

T1+T2 Surge Arrester



■ 3pole surge arrester is suitable for TN-C system.

		TY-12.5M 150 3P	TY-12.5M 275 3P	TY-12.5M 320 3P
SPD classification according to EN61643-11		Type 1 + Type 2	Type 1 + Type 2	Type 1 + Type 2
SPD classification according to IEC61643-11		Class I + Class II	Class I + Class II	Class I + Class II
Max. continuous operating a.c. voltage	Uc	150V	275V	320V
Lightning impulse current (10/350μs)	Iimp	12.5kA	12.5kA	12.5kA
Nominal discharge current (8/20 μ s)	In	20kA	20kA	20kA
Max. discharge current (8/20 μ s)	I _{max}	65kA	65kA	65kA
Voltage protection level	Up	≤0.8kV	≤1.3kV	≤1.5kV
Specific energy	W/R	39kJ/Ω	39kJ/Ω	39kJ/Ω
Short circuit withstand capacity	I _{sc}	25kA	25kA	25kA
Temporary overvoltage 5s withstand	T _{ov}	195V	335V	415V
Max. backup fuse		160A gG	160A gG	160A gG
Response time	t _A	≤25ns	≤25ns	≤25ns
Operating temperature range	T _u	-40°C~80°C	-40°C~80°C	-40°C~80°C
Operating state/fault indication		green/red	green/red	green/red
Cross-section area (Min.)		4mm ²	4mm ²	4mm ²
Cross-section area (Max.)		35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail		
Enclosure material		Thermoplastic UL94-V0		
Degree of protection		IP20	IP20	IP20